



LUBRICANTS™

POWER TO PERFORM™

ENKLO 68 PREMIUM

SPECIAL FEATURES

ENKLO 68 PREMIUM is blended from deep hydrofinished base stocks and select additives. The additives are designed for optimum compressor operation. The additives are used to enhance the oxidation stability, anti-rust characteristics, anti-wear properties of the oil. The oil has natural demulsification property, low foaming tendency and quick air release property.

ENKLO 68 Premium is designed for improved reliability of screw compressor.

- Ensures better lubrication of rotors and bearings thereby reducing heat generation and lowering operating temperatures
- Enhanced wear protection resulting in prolonged maintenance-free equipment life
- Outstanding oxidation and thermal stability
- Excellent hydrolytic stability
- Maintains excellent internal surface cleanliness
- Good protection against corrosion
- Good demulsifying properties
- Low foaming tendency
- Excellent seal compatibility
- Double the drain interval in screw compressor compared to conventional IS:10522 grade hydraulic oils
- ENKLO 68 PREMIUM is tailor made for ELGI SCREW COMPRESSORS

PHYSICO-CHEMICAL PROPERTIES

PARAMETERS	ENKLO 68 PREMIUM
APPEARANCE	Bright & Clear
VISCOSITY, KINEMATIC cSt, (@40°C)	AS PER ISO VG 68
VISCOSITY INDEX	> 100
FLASH POINT (COC), °C, Min.	230

SPECIFICATIONS :

