



LUBRICANTS™

POWER TO PERFORM™

SEETUL N 68 (P) REFRIGERATION COMPRESSOR OILS

SPECIAL FEATURES

SEETUL N 68 (P) grade is refrigeration compressor oil. The grade is formulated from specially selected deep hydro finished lube base stocks to provide low pour point, dryness, good chemical stability.

It is recommended for wide range of refrigeration compressors, both reciprocating as well as rotary, using ammonia and carbon dioxide. It is not recommended for R-12, R-22 and other Freon Refrigerants.

PHYSICO-CHEMICAL PROPERTIES

| | |
|--|------------------|
| Appearance | Bright and Clear |
| Colour ASTM | 1.0 |
| Carbon Residue, Conradson, % Wt | 0.05 |
| Copper Strip Corrosion @ 100°C For 3 hrs | 1 |
| Density @ 29.5°C, g/cc | 0.852 |
| Dielectric Strength, kV | >20 |
| Flash Point, COC, °C | >210 |
| Pour Point, °C | <-27 |
| Neutralisation Number, mg KOH / g | <0.05 |
| Foam Tendency, ml Seq I | NIL |
| Moisture Content, ppm | <100 |
| Kinematic Viscosity @ 40°C, cSt | 65.0 - 73.0 |
| Kinematic Viscosity @ 100°C, cSt | 8.9 |
| Viscosity Index | 100 |