



LUBRICANTS™

POWER TO PERFORM™

SPINTEK EE SERIES

SPINDLE OILS

SPECIAL FEATURES

SPINTEK EE grades of oils are energy efficient premium quality lubricating oils recommended for the lubrication of high speed spindles. They are manufactured from highly refined base oils possessing excellent chemical & oxidation stability. They are further fortified with carefully selected oxidation and rust inhibitors. The rust inhibitor protects bearing surface from rusting and corrosion even in the presence of moisture. A special antiwear additive improves oiliness and reduces friction and wear between the rubbing surfaces to an absolute minimum.

APPLICATION AREA

These oils are recommended for lubrication of textile and machine tools, spindle bearings, timing gears, centrifugal separators, positive displacement blowers and hydraulic systems of certain high precision machine tools. SPINTEK EE 12 grade is approved by atira.

PHYSICO-CHEMICAL PROPERTIES

	SPINTEK EE		
	10	12	22
Flash Point, COC, °C Min.	150	154	160
Pour Point, °C, Max.	(-)6	(-)6	(-)3
Viscosity, Kinematic, cSt @ 40 °C, Avg.	9.9	10	22
Viscosity Index, Min.	90	90	90

PERFORMANCE BENEFITS

- Good oil film strength
- Good demulsibility
- High chemical stability
- Lower fluid friction.
- Energy efficient.
- Resistance to rusting and corrosion