



Castrol Hyspin VG Range

Hydraulic Oils

Description

The Castrol Hyspin™ VG hydraulic oil range is based upon highly refined mineral oil enhanced with rust and oxidation inhibitors.

Application

Castrol Hyspin VG has been specially formulated to provide protection against rust and oxidation while demonstrating good lubricity. Castrol Hyspin VG is also referred to as a "R & O" (Rust and Oxidation) hydraulic oil. This range is designed for use in hydraulic systems which do not need anti-wear performance but where a degree of rust and oxidation resistance is desirable. It is also suitable for pumps which contain silver-plated components. The Hyspin VG range is compatible with the most commonly used nitrile, silicone and fluropolymer seal materials.

Hyspin VG is classified as follows:

- DIN 51502 classification - HL
- ISO 6743/4 - Hydraulic Oils Type HL

Advantages

Compared to conventional Hydraulic oils of the same class Hyspin VG has the following advantages:-

- Good thermal and oxidative stability. Oxidative stability reduces deposit formation, resulting in a cleaner system. This can extend maintenance intervals and lubricant operating life.
- Good protection of yellow metal and ferrous components helps maintain and protect equipment.
- Excellent water separation and hydrolytic stability.

Typical Characteristics

Name	Method	Units	10	15	22	32	46	68	100	150	220
ISO Viscosity Grade	-	-	10	15	22	32	46	68	100	150	220
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	890	870	870	870	880	880	880	880	890
Kinematic Viscosity @ 40°C / 104°	ISO 3104 / ASTM D445	mm ² /s	10	15	22	32	46	68	100	150	220
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	2.4	3.3	4.3	5.4	6.8	8.7	11.2	14.7	18.7
Viscosity Index	ISO 2909 / ASTM D2270	-	-	-	95	95	95	>95	95	95	95
Pour Point	ISO 3016 / ASTM D97	°C/°F	-48 / -54	-30 / -22	-30 / -22	-30 / -22	-30 / -22	-24 / -11	-21 / -6	-18 / 0	-15 / 5
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	170 / 338	195 / 383	205 / 401	220 / 428	240 / 464	240 / 464	250 / 482	255 / 491	260 / 500
Foam Sequence I - tendency / stability	ISO 6247 / ASTM D892	ml/ml	30/0	30/0	30/0	30/0	30/0	30/0	30/0	30/0	30/0
Air Release @ 50°C / 122°F	ISO 9120 / ASTM D3427	min	1	1	1	2	3	5	8	-	-
Water Separation @ 54°C / 129°F (40/37/3)	ISO 6614 / ASTM D1401	min	5	5	5	10	10	15	20	-	-
Rust test - distilled water (24 hrs)	ISO 7120 / ASTM D665A	-	Pass								
Rust test - synthetic seawater (24 hrs)	ISO 7120 / ASTM D665B	-	Pass								

Subject to usual manufacturing tolerances.

Castrol Hyspin VG Range

13 May 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre, Whitchurch Hill, Pangbourne, Reading, RG8 7QR, United Kingdom

<http://msdspds.castrol.com>